

Lighting

V2iLumenAir

High Output and PAR LED Luminaire, integrated WiFi fully controllable via a smartphone or tablet via the V2 ilumenAir App.

- Three separate channels - 12k white, 640nm red and a mixed colour channel of 465nm blue and NUV [410nm Violet].
- Built in timings and dimming with a range of effects including storm function, cloud function, sunrise, sunset, twilight and moonlight.
- Acclimation function - gradually adjusts the lighting output of the light over a 10 day period to help prevent light shock.
- Multiple levels of power and colour control.
- Thermal cut out to prevent over heating.



V2iLumenAir

Code	Product	Optimum Aquarium Size (mm)	Dimensions (mm)	Input	Total Power (w)	Total Luminous Flux (lm)	LEDs			
							White 12000 K	Red 640nm	NUV410nm	Blue 465nm
9230	V2iLumenAir Compact*	450 x 450 x 450	200 x 260 x 39	100-240V 50/60Hz	50	2200	20W	2W	2W	20W
5241	V2ilumenAir 900**	730-1200 long x 300- 880 wide	690 x 260 x 39	100-240V 50/60Hz	170	10000	71W	22W	3W	71W
5242	V2ilumenAir 1200**	840-1300 long x 300- 880 wide	805 x 260 x 39	100-240V 50/60Hz	215	13000	90W	22W	4W	95W

* Supplied with fully adjustable tank mount system that allows for easy adjustment of height and positioning over the Aquarium.

** Supplied with easy to use tank mounting system. [Suspension kit - Code 9203 available separately]



V2ilumenAir

